



ARGO-1500-EM

CLEVERTRONICS Argo 1500mm Weatherproof Emergency Batten, Switchable Colour



PRODUCT INFORMATION

Part Number	ARGO-1500-EM
MIC	AUB03520140001
Description	Argo 1500mm Weatherproof Emergency Batten, Switchable Colour
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	1565mm x 121mm x 88mm
Weight	3.1 kg
Diffuser	Polycarbonate
Driver / Ballast	LED Driver - Xitanium, 72w, 1.2-1.4A, 51V DS 230V
Lamp(s)	LED strip module, 3000K / 5700K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 168,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 84,000hr L90/B10 Ta 40°C; LM80 Report 37,000hr, Projected 37,000hr
Operating Voltage	240V AC; 50Hz
Total lumen output	6085lm (120lm/W @4000K, based on non-emergency), details see table below
Power Consumption	see table below
IP Rating	IP65
Operating Temperature	0°C to 40°C
Impact Rating	IK08
AS2293 Classification	C ₀ =D50 C ₉₀ =D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560050	BATT:Eco Lith 3.2V 3.2Ah 70mm lead, no BRKT
AUM03570030001	Lifelight:2LED, Eco, NM, Control Only,3.2Ah, 400mA
1330108	LED Driver - Xitanium, 72w, 1.2-1.4A, 51V DS 230V
8002700	PCA:LED Strip 2S4P, Eco Argonaut (EM)

Colour	Power Consumption			Total Lumen Output
	MAX Charge Lamp ON	Standby Lamp ON	Standby Lamp OFF	
3000K	54.9 W	54.0 W	0.4 W	5583 lm
4000K	51.9 W	51.0 W	0.4 W	6085 lm
5700K	54.5 W	53.6 W	0.4 W	5677 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order