



CBKLEDS-HV-WHT

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE – WHITE



PRODUCT INFORMATION

Part Number	CBKLEDS-HV-WHT
MIC	AUS02820050001
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, White
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Supply Current	0.071A
Power Factor	0.93
Total Lumen Output	1945lm @ 121lm/W (based on non-emergency version)
Power Consumption	21 Watts (MAX Lamps ON), 1.3 Watts (Standby Lamp OFF)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D32 C90=D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
1330049	LED Driver - LC 20w 350/500/700mA flexC SR ADV
8002801	PCA: CLE 220mm 2500lm 840 ADV4 EM SO
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Lifelight, Control Only, HV, LP, No Plug (incl. Hive Node)
8003195	PCA: RF Node CT10678-A7 Ext Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order