



CBKLEDS-MS-DALI-GRY

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE
WITH MICROWAVE SENSOR – GREY



PRODUCT INFORMATION

Part Number	CBKLEDS-MS-DALI-GRY
MIC	AUS02220130102
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire with Microwave Sensor Control of the Lamps (On/Off), Grey
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total Lumen Output	1945lm @ 121lm/W (based on non-emergency version)
Power Consumption	21.8 Watts (MAX Lamps ON), 1.8 Watts (Standby Lamp OFF)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D32 C90=D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
8002801	LED Panel: PCA: CLE 220mm 2500lm 840 ADV4 EM SO
1330051	LED Driver - LC 20w 500mA, SC ADV
1190310	SENSOR:M/Wave Motion Remote MC015S/D
AUM02270170002 CLIFE-CKIT-DALI-NP	Lifelight, Control Only, Dali Reg, LP, No Plug (incl. DALI Node)
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order