



CBKLEDS-WW-DD-HV-WHT

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE
WARM WHITE WITH DALI DRIVER - WHITE



PRODUCT INFORMATION

Part Number	CBKLEDS-WW-DD-HV-WHT
MIC	AUS02820130001
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire Warm White with Dali Driver, White Body
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
LED Driver	Tridonic LCA 17W 250-700mA one4all SC PRE (DALI)
Lamp(s)	LED module, 3,000K Warm White, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total Lumen Output	1850lm @ (116lm/W non-emergency version)
Power Consumption	17 Watts (Lamps ON), 1.3 Watts (Lamp OFF)
IP Rating	IP65
Impact Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D32 C90=D32(Ceiling Mount), C0=D5 C90=D5 (Wall Mount)
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Lifelight, Control Only, HV, LP, No Plug (incl Hive node)
1330045	LED Driver - 17w 250-700mA, Dimm
8002802	LED: PCA: CLE 220mm 2500lm 830 ADV4 EM SO
8003195	PCA: RF Node CT10678-A7 Ext Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order