



CLIFE-PRO-BLK

CLEVERTRONICS CLP LIFELIGHT PRO, BLACK



PRODUCT INFORMATION					
Part Number	CLIFE-PRO-BLK				
MIC	UKT02310040001				
Description	CLP Premium LifeLight PRO, High Performance, Recessed Emergency Light, Black, with Clevertest Plus Enabled				
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear				
Mounting	Recessed Mount				
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)				
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)				
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)				
Weight	0.6kg				
Operating Mode	Non-maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	2 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	398lm (Emergency)				
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C (Lifelight Head) 0°C to 60°C (Driver)				
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 				
Luminaire Classification	<table border="1" style="display: inline-table;"> <tr> <td>X</td> <td>0</td> <td>AD</td> <td>180</td> </tr> </table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598.2.22, BS 5266				

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



CLIFE-PRO-BLK

CLEVERTRONICS CLP LIFELIGHT PRO, BLACK

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550229	BATT:LP 3.2V 6400mAh 200mm lead, Sleeve
1100894	UK,LifelightPro HeadAssbly,Rnd,LargeRg,Gen2,Blk,LT
UKM02370070001	CLIFE-PRO-CKIT-475, LifelightPro, Control Only, 475mA, LP, OWC

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice