

CLEVERTRONICS CLP LIFELIGHT PRO SURFACE MOUNT EMERGENCY (DALI)



PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SM-DALI
MIC	UKT02210030002
Description	CLP Premium LifeLight PRO, High Performance, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	350lm (Emergency)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts 			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt
8002908	PCA: CT10142-L9 2C250/475mA CTP UK Vert Connectors
8003060	PCA: DALI Node #CT10629-Ax

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.