



CLIFE-PRO-SMC

CLEVERTRONICS CLP LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION

| | |
|-----------------------------|--|
| Part Number | CLIFE-PRO-SMC |
| MIC | UKT02510040201 |
| Description | CLP Premium Lifelight PRO, High Performance, Cylinder Surface Mount Emergency Light, Clevertest Plus Enabled |
| Construction | Powder coated metal enclosure, PC/ABS head |
| Dimensions L x W x H | 128mm Diameter, 245mm Height |
| Operating Mode | Non-maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery Type & Manufacturer | Lithium Iron Phosphate (LiFePO4), Clevertronics |
| Charging Method | Intelligent current limited constant voltage |
| Lamp(s) | 2 x LED |
| Operating Voltage | 220-240V AC; 50Hz |
| Power Consumption | 0.4Watts (Standby), 2.7Watts (Max) |
| Total lumen output | 380lm (Emergency) |

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



CLIFE-PRO-SMC

CLEVERTRONICS CLP LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY

PRODUCT INFORMATION

| | | | | | |
|-------------------------------|---|----|-----|----|-----|
| Rated Emergency Duration | 180 minutes | | | | |
| IP Rating | IP20 | | | | |
| Maximum Case Temperature (TC) | 50°C (no heatsink required for lamp control gear) | | | | |
| Operating temperature | 0°C to 40°C | | | | |
| Protection | <ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts | | | | |
| Luminaire Classification | <table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table> | X | 0 | AD | 180 |
| X | 0 | AD | 180 | | |
| Conformity | BS EN 60598-2-22, BS 5266 | | | | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|--|--|
| 1550230 | BATT:LP 3.2V 6400mAh.200mm lead. BRKT |
| 1100811 | UK,Lifelight Pro,Head Assem,Ld:280mm,Round,Gen2,LT |
| UKM02370030002 CLIFE-PRO-SMS-CKIT-IC2-475 | Lifelight Pro Control Only, 475mA, LP, CTP, OWC |

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.