



## CLIFE-SM-WP-HVG

CLEVERTRONICS CLP LIFELIGHT IP65 WEATHERPROOF  
SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION					
Part Number	CLIFE-SM-WP-HVG				
MIC	UKD02820010001				
Description	CLP Premium Lifelight, High Performance, Weatherproof, Surface Mounted Emergency Light				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	1 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	200lm (Emergency)				
Power Consumption	1.3W (Standby) 4.5W (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li></ul>				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598.2.22, BS 5266				

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



**CLIFE-SM-WP-HVG**  
CLEVERTRONICS CLP LIFELIGHT IP65 WEATHERPROOF  
SURFACE MOUNT EMERGENCY

**REPLACEMENT PARTS**

<b>PART NUMBER</b>	<b>DESCRIPTION</b>
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8050174	HWSUB: CT10694-D1 (Lifelight Head)
8002918	PCA: CLIFE CT10260-L5 1C500 HIVE Vert Conn (Driver)
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice