



CLEVERTRONICS LP SWINGBLADE LED EXIT, BLACK



PRODUCT INFORMATION

Catalogue Number	CSBLED-BLK
Description	LP Premium Swingblade Emergency Exit, Black
Construction	Metal frame, Black End Caps with Acrylic & Polycarbonate Diffuser
Mounting	Surface Mount, Wall or Ceiling on a slide connect bracket – Single & Double Sided “NOTE: If product is suspended below the ceiling or mounted on a metal surface the Swingblade bracket cover plate accessory (P/N: 2740105) is required to cover the mains terminals”
Dimensions L x W x H	See diagram above
Operating Mode	Maintained
Testing System	N/A - Manual test switch
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	24 x High intensity LED, surface mounted onto a replaceable lamp bar - 100,000hour
Operating Voltage	240V AC; 50Hz
Power Consumption	3.8 Watts (Standby), 6.2 Watts during first 16hr charge
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D10 C90=E3.2
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550070	BATT:LP 3.2V 3200mAh 220mm lead, sp.BRKT
8002355	PCA:Lithium S/BLADE Driver. #CT10164-L4.
8002185	PCA:24DLED SB LED Strip, #CT10156-D2

