



LCFLED-HVG CLEVERTRONICS L10 CLEVERFIT EXIT



PRODUCT INFORMATION	
Part Number	LCFLED-HVG
MIC	UKA01810010001
Description	L10 Optimum Cleverfit Emergency Exit
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.7 Watts (Standby), 4.5 Watts (Max)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LCFLED-HVG

CLEVERTRONICS L10 CLEVERFIT EXIT

PRODUCT INFORMATION

Viewing Distance	30m				
Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)				
Luminaire Classification	<table border="1"><tr><td>X</td><td>1</td><td>AFG</td><td>180</td></tr></table>	X	1	AFG	180
X	1	AFG	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530090	BATTERY: L10 3.3V 2.5AH 390mm lead,noBrkt
8002710	LED: PCA:DurisLED Strip Clvrft Pro CT10276-D3
8002337	DRIVER: PCA:LCFLED Driver CT10164-L6 6C70 CTP UK OWC
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice