

CLEVERTRONICS L10 CLEVERFIT EXIT



PRODUCT INFORMATION

| | |
|-------------------------------|---|
| Catalogue Number | LCFLED |
| MIC | UKA01310010002 |
| Description | L10 Lithium Nanophosphate Cleverfit Emergency Exit with Clevertest Plus Enabled |
| Construction | ABS body and Diffuser with Polycarbonate Clear Tamper proof Cover |
| Mounting | Wall, Ceiling Single-Sided & Ceiling Double-Sided |
| Dimensions L x W x H | 355mm x 80mm x 215mm |
| Weight | 1.2kg |
| Operating Mode | Maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery Type and Manufacturer | Lithium Nanophosphate (LiFePO4), Clevertronics |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | All directional inserts included in the box |
| Lamp(s) | 6 x Duris E5 LED, 100,000 hours |
| Operating Voltage | 220-240V AC; 50Hz |
| Power Factor | 0.45 |
| Power Consumption | 2.5 Watts (Standby), 4.5 Watts (Max) |

PRODUCT INFORMATION

| | | | | |
|--------------------------|---|---|----|-----|
| Viewing Distance | 30m | | | |
| Rated Emergency Duration | 180 minutes | | | |
| IP Rating | IP20 | | | |
| Operating temperature | 0°C to 40°C | | | |
| Protection | <ul style="list-style-type: none"> • Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) | | | |
| Luminaire Classification | X | 1 | AG | 180 |
| Conformity | BS EN 60598.2.22, BS 5266 | | | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|--|
| 1530090 | BATTERY:L10 3.3V 2.5AH 390mm lead,noBrkt |
| 8002710 | PCA:DurisLED Strip Clvrft Pro CT10276-D3 |
| 8002338 | PCA:LCFLED Driver CT10164-L6 6C70 CTP UK OWC |

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.