

## CLEVERTRONICS L10 LIFELIGHT PRO SURFACE MOUNT EMERGENCY (DALI)



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SM-DALI
MIC	UKT01210010002
Description	L10 Optimum LifeLight PRO, High Performance, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery Type and Manufacturer	Lithium Iron Phosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	357lm (Emergency)
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)

## PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> <li>• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts</li> </ul>			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

## REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	BATTERY:L10 3.3V 5AH. 200mm lead.no Brkt
8002958	PCA: CT10142-L9 2C250/415 CTP D DR ZW HVG UK V CON
8003060	PCA: DALI Node #CT10629-Ax

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.