



LLIFE-PRO-SM-WP-HVG

CLEVERTRONICS L10 LIFELIGHT PRO IP65 WEATHERPROOF
SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION					
Part Number	LLIFE-PRO-SM-WP-HVG				
MIC	UKT01820040001				
Description	L10 Optimum Lifelight PRO, High Performance, Weatherproof, Surface Mounted Emergency Light				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Zoneworks XT HIVE (RF)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	2 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	333lm (Emergency) with Area Lens				
Power Consumption	0.7W (Standby) 3.0W (Max)				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice



LLIFE-PRO-SM-WP-HVG

CLEVERTRONICS L10 LIFELIGHT PRO IP65 WEATHERPROOF
SURFACE MOUNT EMERGENCY

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	BATTERY:L10 3.3V 5AH. 200mm lead, no Brkt
8050170	HWSUB: CT10668-D1 (Lifelight Head)
8002958	PCA: CT10142-L9 2C250/415 CTP D DR ZW HVG UK V CON
8003330	PCA: 2.4Ghz RF Node CT10748-A1 Int Antenna

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice