



LLIFE-PRO-WP-IPREM

CLEVERTRONICS L10 LIFELIGHT PRO IP66/67 WEATHERPROOF
EMERGENCY WITH REMOTE CONTROL GEAR



PRODUCT INFORMATION

Part Number	LLIFE-PRO-WP-IPREM
MIC	UKT01320110001
Description	L10 Optimum Lifelight PRO, High Performance, Surface Mount Emergency with IP66/67 Head and Remote-Control Gear, Enabled with Clevertest Plus
Construction	Polycarbonate
Dimensions L x W x H	122mm x 120mm x 75mm (Lamp Head Enclosure) 380mm x 190mm x 130mm (Control Pack)
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4Watts (Standby), 2.7Watts (Max)
Total lumen output	322lm

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



LLIFE-PRO-WP-IPREM

CLEVERTRONICS L10 LIFELIGHT PRO IP66/67 WEATHERPROOF
EMERGENCY WITH REMOTE CONTROL GEAR

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP66/67				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt
1100698	UK, Lifelight Pro, WP Head, LT, Gen 2
UKM01370180001 LLIFE-PRO-CKIT-415	Lifelight Pro, Control Only, 415mA, L10, CTP, OWC

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.