

CLEVERTRONICS L10 ARGONAUT VANDAL BATTEN



PRODUCT INFORMATION

Catalogue Number	LVP2LEDM-P
MIC	AUB01330020001
Description	L10 Optimum 2ft Argonaut LED Vandal Batten with Battery POD and LED Modules/Light Engines
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	790mm x 140mm x 120mm (including battery POD)
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws, LSZH
Driver / Ballast	Tridonic LC 50W 350-1050mA
Lamp(s)	1 x LED module, 4000K natural white, 100,000h [L80/ B20, Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2529 lm @109lm/W (based on non-emergency version @23W)
Power Consumption	27W (MAX charging-Lamp ON), 23W (Standby Lamp ON), 1.3W (Standby Lamp OFF)
IP Rating	IP66
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D32
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10 6.6V 2500mA.SBS. (2)
1330055	LED Driver - LC 50w 1050mA, fleC Ip EXC
8002699	PCA: LED Strip 5P8S, ALS-50-840-3-01-A
LCPLED-38V120C-CKIT-ZW	LED Power Pack, 38V 120mA, 6.6V 2.5Ah,L10

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order